

Tech Specs | SOHO • B One Plus



Quick Look

Number of Ethernet WAN port

Number of Ethernet LAN port

4 (GE)

Router Throughput

1Gbps

SpeedFusion VPN Throughput (No Encryption)

400Mbps

SpeedFusion VPN Throughput (256-bit AES)

200Mbps

Number of Cellular Modem

Interfaces

Maximum Ethernet WAN / LAN port configuration

2 WAN with 4 LAN

SFP LAN / WAN

No

Serial Interface

No Wi-Fi AP

Yes

Wi-Fi WAN

Yes **USB WAN**

Yes (1x USB-C)

Module Expansion

Performance

Number of Recommended Users Maximum Number of AP Supported 30 / 50 [1] [1] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

Cellular Modem Category options

1x CAT-4

5G support

No

SIM Slots

SIM Card Size Nano-SIM (4FF)

Wi-Fi Radio

Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 6

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)

Wi-Fi Antenna Transmit Power (5GHz, single chain)

24dBm

Multiple SSIDs

16

GPS

RemoteSIM (used in SIM Injector)

Yes (HW2+)

FusionSIM

Yes (HW2+)

Peplink eSIM Data Plans

Yes

[2]

[2] Models with selected SKU support eSIM.

BYO eSIM

Yes

Features

SpeedFusion Hot Failover

Yes

[3] Require PrimeCare Subscription, complimentary for the first year.

SpeedFusion Smoothing

[3]

[3] Require PrimeCare Subscription, complimentary for the first year.

SpeedFusion Bandwidth Bonding

Yes

[3]

[3] Require PrimeCare Subscription, complimentary for the first year.

SpeedFusion Connect

Yes

[4] PrimeCare subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.

SpeedFusion Relay Mode (Server)

Drop-In Mode

High Availability

Yes Peplink AP Series Management Remote AP & Multiple Config Profiles Management No WAN as LAN No LAN Bypass No InTouch Yes Virtual WAN Yes [5] [5] 1 Virtual WAN complimentary with active PrimeCare. Up to 3 Virtual WAN upon purchasing Virtual WAN Activation Licence. Synergy Mode (Controller) Synergized Device Yes Application and Web Blocking Yes Web Content Filtering IP Passthrough IPv6 No x.509 Certificate Yes [6] Require IPsec X.509 Certificate License Key Captive Portal Yes **GPIO** Yes Ignition Sensing No Netflow support LACP (802.3ad) NIC Bonding

No

Internal Storage for Edge Computing

External Storage via USB Port

Yes

[7] Require software add-on licence and Firmware 8.5.2 or above to enable edge computing (Docker). Dead Reckoning

No

Core Functionality

Inter-VLAN Routing

Yes

802.1q VLANs Supported

Port-Based VLAN

Load Balancing Algorithms

Load Balancing & Failover

Yes Inbound Load Balancing InControl 2 Cloud Management

InControl GPS Fleet Management

Advanced QoS Functionality

Bandwidth Usage Monitoring

QoS for VoIP and E-Commerce

User Groups Bandwidth Control

Yes

VPN Functionality

SpeedFusion VPN

Yes

Number of SpeedFusion VPN Peers

2 or 5

[8]

[8] 2 SpeedFusion VPN Peers are enabled by default. 5 SpeedFusion VPN Peers are enabled with PrimeCare Subscription, complimentary for the first year.

IPsec VPN

Yes

Number of IPsec Tunnels

L2TP VPN / Open VPN / PPTP VPN Server

Maximum PPTP / L2TP / OpenVPN Users

3

Remote RADIUS / LDAP authentication in Remote User Access

Number of OpenVPN Tunnel (Site to Site)

Number of GRE Tunnel (Site to Site)

Hardware

Enclosure

Indoor, Plastic

4pin Molex Micro-Fit Connector

Terminal Block Power Connector for Mobile / Vehicular Deployment

AC Adapter or PSU

AC Input 100V-240V, DC Output 12V 3A

Input voltage

DC 10-30V

PoE Input

No

PoE Output

No

USB Power Input

Nominal Power Consumption

6W

Maximum Power Consumption

17W

[9]

[9] Maximum without USB-C output.

Dimensions in inches

10.31 x 6.33 x 1.31inch

Dimensions in mm

262 x 161 x 33.5mm

202 / 101 / 95:5111

Weight (Pound)

1.7 pounds

Weight (Gram / Kilogram)

761 grams

Operating Temperature

-40°-113°F, -40°-45°C

Humidity

10%-90% (non-condensing)

Rack-mount

No

Dual Hot Swap Power Supply

No

Warranty Info

Warranty

1-Year Limited Warranty