

Tech Specs | SOHO • B One



Quick Look

Number of Ethernet WAN port

2 (GF)

Number of Ethernet LAN port

4 (GE)

Router Throughput

1Gbps

SpeedFusion VPN Throughput (No Encryption)

400Mbps

SpeedFusion VPN Throughput (256-bit AES)

200Mbps

Number of Cellular Modem

Number

Interfaces

Maximum Ethernet WAN / LAN port configuration

2 WAN with 4 LAN

SFP LAN / WAN

No

Serial Interface

No

Wi-Fi AP

Yes

Yes

Wi-Fi WAN

USB WAN

Yes (1x USB-C)

Module Expansion

· ·

No

Performance

Number of Recommended Users Maximum Number of AP Supported 30 / 50 [1]

[1] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

Cellular Modem Category options

No

5G support

No

SIM Slots No

SIM Card Size

No Wi-Fi Radio

Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 6

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)

Wi-Fi Antenna Transmit Power (5GHz, single chain)

24dBm

Multiple SSIDs

16

GPS No

RemoteSIM (used in SIM Injector)

No

FusionSIM

No

Peplink eSIM Data Plans

No

BYO eSIM No

Features

SpeedFusion Hot Failover

Yes

[2]

[2] Require PrimeCare Subscription, complimentary for the first year.

SpeedFusion Smoothing

Yes

[2]

[2] Require PrimeCare Subscription, complimentary for the first year.

SpeedFusion Bandwidth Bonding

Yes

[2]

[2] Require PrimeCare Subscription, complimentary for the first year.

SpeedFusion Connect

Yes

[3] PrimeCare subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.

SpeedFusion Relay Mode (Server)

Yes

Drop-In Mode

High Availability

Peplink AP Series Management

Yes Remote AP & Multiple Config Profiles Management WAN as LAN No LAN Bypass No InTouch Yes Virtual WAN Yes [4] [4] 1 Virtual WAN complimentary with active PrimeCare. Up to 3 Virtual WAN upon purchasing Virtual WAN Activation Licence. Synergy Mode (Controller) Synergized Device Application and Web Blocking Yes Web Content Filtering Lite IP Passthrough Yes [5] [5] Available for Firmware 8.5.0 or above. IPv6 No x.509 Certificate Yes [6] Require IPsec X.509 Certificate License Key Captive Portal Yes **GPIO**

Yes

Ignition Sensing

No

Netflow support

LACP (802.3ad) NIC Bonding

No

Internal Storage for Edge Computing

External Storage via USB Port

Yes

[7] Require software add-on licence and Firmware 8.5.2 or above to enable edge computing (Docker). Dead Reckoning

No

Core Functionality

Inter-VLAN Routing

Yes

802.1q VLANs Supported

Port-Based VLAN

Load Balancing Algorithms

Load Balancing & Failover

Yes Inbound Load Balancing InControl 2 Cloud Management

InControl GPS Fleet Management

Advanced QoS Functionality

Bandwidth Usage Monitoring

QoS for VoIP and E-Commerce

User Groups Bandwidth Control

Yes

VPN Functionality

SpeedFusion VPN

Yes

Number of SpeedFusion VPN Peers

2 or 5

[8]

[8] 2 SpeedFusion VPN Peers are enabled by default. 5 SpeedFusion VPN Peers are enabled with PrimeCare Subscription, complimentary for the first year.

IPsec VPN

Yes

Number of IPsec Tunnels

L2TP VPN / Open VPN / PPTP VPN Server

Maximum PPTP / L2TP / OpenVPN Users

3

Remote RADIUS / LDAP authentication in Remote User Access

Number of OpenVPN Tunnel (Site to Site)

Number of GRE Tunnel (Site to Site)

Hardware

Enclosure

Indoor, Plastic

4pin Molex Micro-Fit Connector

Terminal Block Power Connector for Mobile / Vehicular Deployment

AC Adapter or PSU

AC Input 100V-240V, DC Output 12V 3A

Input voltage

DC 10-30V

PoE Input

No

PoE Output

No

USB Power Input

Nominal Power Consumption

6W

Maximum Power Consumption

[9]

[9] Maximum without USB-C output.

Dimensions in inches

10.31 x 6.33 x 1.31inch

Dimensions in mm

262 x 161 x 33.5mm

Weight (Pound)

1.6 pounds

Weight (Gram / Kilogram)

727 grams

Operating Temperature

-40°-113°F, -40°-45°C

Humidity

10%-90% (non-condensing)

Rack-mount

No

Dual Hot Swap Power Supply

No

Warranty Info

Warranty

1-Year Limited Warranty