





## Quick Look

- Number of Ethernet WAN port  
2 (GE)
- Number of Ethernet LAN port  
9 (GE)
- Router Throughput  
2.5Gbps
- SpeedFusion VPN Throughput (No Encryption)  
600Mbps
- SpeedFusion VPN Throughput (256-bit AES)  
500Mbps
- Number of Cellular Modem  
1

## Interfaces

- Maximum Ethernet WAN / LAN port configuration  
2 WAN with 9 LAN
- SFP LAN / WAN  
No
- Serial Interface  
No
- Wi-Fi AP  
No
- Wi-Fi WAN  
No
- USB WAN  
Yes (2x USB)
- Module Expansion  
Yes (Expansion Module for Balance 310X)

## Performance

Maximum Number of AP Supported  
50  
Number of Recommended Users  
50–500

## Wireless details

Cellular Modem Category options  
1x CAT-12, 1x CAT-20, 1x 5G  
5G support  
Yes  
SIM Slots  
2  
SIM Card Size  
Mini-SIM (2FF)  
Wi-Fi Radio  
No  
Wi-Fi Antenna Transmit Power (2.4GHz, single chain)  
No  
Wi-Fi Antenna Transmit Power (5GHz, single chain)  
No  
Multiple SSIDs  
No  
GPS  
Yes  
RemoteSIM (used in SIM Injector)  
Yes  
FusionSIM  
Yes  
Peplink eSIM Data Plans  
Yes (HW4+)  
[1]  
[1] Require Firmware 8.3.0 or above and supported for selected SKU.  
BYO eSIM  
Yes (HW4+)  
[2]  
[2] Require Firmware 8.4.0 or above and supported for selected SKU.

## Features

SpeedFusion Hot Failover  
Yes  
SpeedFusion Smoothing  
Yes  
SpeedFusion Bandwidth Bonding  
Yes  
SpeedFusion Connect  
Yes  
[3]  
[3] CarePlan subscription includes 1TB/year complimentary SpeedFusion Connect Usage data.  
SpeedFusion Relay Mode (Server)  
Yes  
Drop-In Mode  
Yes  
High Availability  
Yes  
Peplink AP Series Management  
Yes  
Remote AP & Multiple Config Profiles Management  
Yes  
WAN as LAN

No  
LAN Bypass  
No  
InTouch  
Yes (HW4+)  
Virtual WAN  
Yes  
[4]  
[4] Up to 10 Virtual WAN if purchasing Virtual WAN Activation Licence.  
Synergy Mode (Controller)  
Yes (HW4+)  
Synergized Device  
Yes  
Application and Web Blocking  
Yes  
Web Content Filtering  
Full  
IP Passthrough  
Yes  
IPv6  
Yes  
x.509 Certificate  
Yes  
GPIO  
No  
Captive Portal  
Yes  
Ignition Sensing  
No  
Netflow support  
Yes  
LACP (802.3ad) NIC Bonding  
Yes  
[5]  
[5] Require Firmware 8.4.1 or above.  
Internal Storage for Edge Computing  
No  
External Storage via USB Port  
Yes  
[6]  
[6] Require Firmware 8.4.0 or above. Support Docker.  
Dead Reckoning  
No

## Core Functionality

Inter-VLAN Routing  
Yes  
802.1q VLANs Supported  
1024  
Port-Based VLAN  
Yes  
Load Balancing & Failover  
Yes  
Load Balancing Algorithms  
8  
Inbound Load Balancing  
Yes  
InControl 2 Cloud Management  
Yes  
InControl GPS Fleet Management

Yes

## Advanced QoS Functionality

Bandwidth Usage Monitoring

Yes

QoS for VoIP and E-Commerce

Yes

User Groups Bandwidth Control

Yes

## VPN Functionality

SpeedFusion VPN

Yes

Number of SpeedFusion VPN Peers

3 or 30

[7]

[7] PepVPN/SpeedFusion Peers license, it can change the maximum number of PepVPN/SpeedFusion peer.Balance 310X,SFN-LC-30.

Up to 30 PepVPN/SpeedFusion peers and SpeedFusion Bonding License Key.

IPsec VPN

Yes

Number of IPsec Tunnels

40

L2TP VPN / Open VPN / PPTP VPN Server

Yes

Maximum PPTP / L2TP / OpenVPN Users

50

Remote RADIUS / LDAP authentication in Remote User Access

Yes

Number of OpenVPN Tunnel (Site to Site)

5

Number of GRE Tunnel (Site to Site)

5

## Hardware

Enclosure

Indoor, Metal

4pin Molex Micro-Fit Connector

No

Terminal Block Power Connector for Mobile / Vehicular Deployment

No

AC Adapter or PSU

24V 2.5A (ACW-647)

Input voltage

DC 12–30V

PoE Input

No

PoE Output

No

USB Power Input

No

Nominal Power Consumption

NA

Maximum Power Consumption

30W

Dimensions in inches

1.7 x 11.5 x 7.0 inches

Dimensions in mm

43 x 292 x 177 mm  
Weight (Pound)  
7.28 pounds  
Weight (Gram / Kilogram)  
3.3 kg  
Operating Temperature  
-40°–149°F, -40°–65°C  
Humidity  
15%–95% (non-condensing)  
Rack-mount  
1U  
Dual Hot Swap Power Supply  
No

Warranty Info

Warranty  
1-Year Limited Warranty