





## Quick Look

Number of Ethernet WAN port

2 / 5 (GE)

[1]

[1] If the WAN Activation License (BPL-ONE-LC-5WAN) is activated, Ethernet WAN port number is changed to 5, Ethernet LAN to 5, router Stateful Firewall becomes 400Mbps.

Number of Ethernet LAN port

8 / 5 (GE)

[1]

[1] If the WAN Activation License (BPL-ONE-LC-5WAN) is activated, Ethernet WAN port number is changed to 5, Ethernet LAN to 5, router Stateful Firewall becomes 400Mbps.

Router Throughput

600Mbps/, 400Mbps

[1]

[1] If the WAN Activation License (BPL-ONE-LC-5WAN) is activated, Ethernet WAN port number is changed to 5, Ethernet LAN to 5, router Stateful Firewall becomes 400Mbps.

SpeedFusion VPN Throughput (No Encryption)

60Mbps

SpeedFusion VPN Throughput (256-bit AES)

30Mbps

Number of Cellular Modem

No

## Interfaces

Maximum Ethernet WAN / LAN port configuration

5 WAN with 5 LAN, 2 WAN with 8 LAN

SFP LAN / WAN

No

Serial Interface

No

Wi-Fi AP

No

Wi-Fi WAN  
No  
USB WAN  
Yes (1x USB)  
Module Expansion  
No

Performance

Maximum Number of AP Supported  
30 / 50  
[2]  
[2] 50 AP is available as a license add-on (AP-LC-50).  
Number of Recommended Users  
1–60

Wireless details

Cellular Modem Category options  
No  
5G support  
No  
SIM Slots  
No  
SIM Card Size  
No  
Wi-Fi Radio  
No  
Wi-Fi Antenna Transmit Power (2.4GHz, single chain)  
No  
Wi-Fi Antenna Transmit Power (5GHz, single chain)  
No  
Multiple SSIDs  
No  
GPS  
No  
RemoteSIM (used in SIM Injector)  
No  
FusionSIM  
No  
Peplink eSIM Data Plans  
No  
BYO eSIM  
No

Features

SpeedFusion Hot Failover  
Yes  
[3]  
[3] Require SpeedFusion Bonding License (BPL-ONE-LC-SF).  
SpeedFusion Smoothing  
Yes  
[3]  
[3] Require SpeedFusion Bonding License (BPL-ONE-LC-SF).  
SpeedFusion Bandwidth Bonding  
Yes  
[3]  
[3] Require SpeedFusion Bonding License (BPL-ONE-LC-SF).  
SpeedFusion Connect

Yes  
[4]  
[4] CarePlan subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.  
SpeedFusion Relay Mode (Server)  
Yes  
Drop-In Mode  
Yes  
High Availability  
Yes  
Peplink AP Series Management  
Yes  
Remote AP & Multiple Config Profiles Management  
No  
WAN as LAN  
Yes  
LAN Bypass  
No  
InTouch  
Yes  
Virtual WAN  
Yes  
[5]  
[5] Up to 3 Virtual WAN if purchasing Virtual WAN Activation Licence.  
Synergy Mode (Controller)  
Yes  
Synergized Device  
Yes  
Application and Web Blocking  
Yes  
Web Content Filtering  
Lite  
IP Passthrough  
Yes  
IPv6  
Yes  
x.509 Certificate  
Yes  
GPIO  
No  
Captive Portal  
Yes  
Ignition Sensing  
No  
Netflow support  
Yes  
LACP (802.3ad) NIC Bonding  
No  
Internal Storage for Edge Computing  
No  
External Storage via USB Port  
No  
Dead Reckoning  
No

Core Functionality

Inter-VLAN Routing  
Yes  
802.1q VLANs Supported  
128  
Port-Based VLAN

Yes  
Load Balancing & Failover  
Yes  
Load Balancing Algorithms  
8  
Inbound Load Balancing  
No  
InControl 2 Cloud Management  
Yes  
InControl GPS Fleet Management  
No

## Advanced QoS Functionality

Bandwidth Usage Monitoring  
Yes  
QoS for VoIP and E-Commerce  
Yes  
User Groups Bandwidth Control  
Yes

## VPN Functionality

SpeedFusion VPN  
Yes  
Number of SpeedFusion VPN Peers  
3 or 5 or 20  
[6]  
[6] PepVPN/SpeedFusion Peers license, it can change the maximum number of PepVPN/SpeedFusion peer.PVN-LC-05. Up to 5  
PepVPN/SpeedFusion peers.PVN-LC-10. Up to 10 PepVPN/SpeedFusion peers.PVN-LC-20. Up to 20 PepVPN/SpeedFusion peers.  
IPsec VPN  
Yes  
Number of IPsec Tunnels  
5  
L2TP VPN / Open VPN / PPTP VPN Server  
Yes  
Maximum PPTP / L2TP / OpenVPN Users  
15  
Remote RADIUS / LDAP authentication in Remote User Access  
No  
Number of OpenVPN Tunnel (Site to Site)  
5  
Number of GRE Tunnel (Site to Site)  
5

## Hardware

Enclosure  
Indoor, Metal  
4pin Molex Micro-Fit Connector  
No  
Terminal Block Power Connector for Mobile / Vehicular Deployment  
No  
AC Adapter or PSU  
12V 2A PSU (ACW-601)  
Input voltage  
DC 12–24V  
PoE Input  
No  
PoE Output

No  
USB Power Input  
No  
Nominal Power Consumption  
NA  
Maximum Power Consumption  
15W  
Dimensions in inches  
10.7 x 6.3 x 1.2 inches  
Dimensions in mm  
271 x 160 x 30 mm  
Weight (Pound)  
1.22 pounds  
Weight (Gram / Kilogram)  
0.56 kg  
Operating Temperature  
23°–113°F, -5°–45°C  
Humidity  
NA  
Rack-mount  
No  
Dual Hot Swap Power Supply  
No

Warranty Info

Warranty  
1-Year Limited Warranty