



### Quick Look

Number of Ethernet WAN port	1 (GE)
Number of Ethernet LAN port	2 (GE)
Router Throughput	100Mbps
SpeedFusion VPN Throughput (No Encryption)	40Mbps
SpeedFusion VPN Throughput (256-bit AES)	20Mbps
Number of Cellular Modem	1

### Interfaces

Maximum Ethernet WAN / LAN port configuration	1 WAN with 2 LAN, 0 WAN with 3 LAN
SFP LAN / WAN	No
Serial Interface	No
Wi-Fi AP	Yes
Wi-Fi WAN	Yes
USB WAN	No

Module Expansion	No
------------------	----

## Performance

---

Number of Recommended Users	1–60
-----------------------------	------

Maximum Number of AP Supported	No
--------------------------------	----

## Wireless details

---

Cellular Modem Category options	1x CAT-4, 1x CAT-6
---------------------------------	-----------------------

5G support	No
------------	----

SIM Slots	2
-----------	---

SIM Card Size	Mini-SIM (2FF)
---------------	----------------

Wi-Fi Radio	Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 5
-------------	--------------------------------------

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	20dBm
---	-------

Wi-Fi Antenna Transmit Power (5GHz, single chain)	21dBm
---	-------

Multiple SSIDs	16
----------------	----

GPS	Yes
-----	-----

RemoteSIM (used in SIM Injector)	Yes (HW4+)
----------------------------------	------------

FusionSIM	Yes (HW4+)
-----------	------------

Peplink eSIM Data Plans	No
-------------------------	----

BYO eSIM	No
----------	----

## Features

SpeedFusion Hot Failover **Yes**

SpeedFusion Smoothing **No**

SpeedFusion Bandwidth Bonding **No**

SpeedFusion Connect **Yes** <sup>[1]</sup>

[1] CarePlan subscription includes 500GB/year complimentary SpeedFusion Connect Usage data.

SpeedFusion Relay Mode (Server) **Yes**

Drop-In Mode **Yes**

High Availability **Yes**

Peplink AP Series Management **No**

Remote AP & Multiple Config Profiles Management **No**

WAN as LAN **Yes**

LAN Bypass **No**

InTouch **Yes (HW2+)**

Virtual WAN **No**

Synergy Mode (Controller) **Yes**

Synergized Device **Yes**

Application and Web Blocking **Yes**

Web Content Filtering **Lite**

IP Passthrough **Yes**

IPv6	No
x.509 Certificate	No
Captive Portal	Yes
GPIO	No
Ignition Sensing	No
Netflow support	No
LACP (802.3ad) NIC Bonding	No
Internal Storage for Edge Computing	No
External Storage via USB Port	No
Dead Reckoning	No

## Core Functionality

---

Inter-VLAN Routing	Yes
802.1q VLANs Supported	16
Port-Based VLAN	Yes
Load Balancing Algorithms	8
Load Balancing & Failover	Yes
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	No

## Advanced QoS Functionality

---

Bandwidth Usage Monitoring	<b>Yes</b>
----------------------------	------------

QoS for VoIP and E-Commerce	<b>Yes</b>
-----------------------------	------------

User Groups Bandwidth Control	<b>Yes</b>
-------------------------------	------------

## VPN Functionality

---

SpeedFusion VPN	<b>Yes</b>
-----------------	------------

Number of SpeedFusion VPN Peers	<b>2</b>
---------------------------------	----------

IPsec VPN	<b>Yes</b>
-----------	------------

Number of IPsec Tunnels	<b>5</b>
-------------------------	----------

L2TP VPN / Open VPN / PPTP VPN Server	<b>Yes</b>
---------------------------------------	------------

Maximum PPTP / L2TP / OpenVPN Users	<b>3</b>
-------------------------------------	----------

Remote RADIUS / LDAP authentication in Remote User Access	<b>No</b>
---	-----------

Number of OpenVPN Tunnel (Site to Site)	<b>5</b>
---	----------

Number of GRE Tunnel (Site to Site)	<b>5</b>
-------------------------------------	----------

## Hardware

---

Enclosure	<b>Outdoor, IP55, Plastic</b>
-----------	---------------------------------------

4pin Molex Micro-Fit Connector	<b>No</b>
--------------------------------	-----------

Terminal Block Power Connector for Mobile / Vehicular Deployment	No	
AC Adapter or PSU	No	
Input voltage	PoE: DC 48–56V	
PoE Input	Yes <sup>[2]</sup>	[2] 802.3at PoE+ or 56V Peplink Passive PoE.
PoE Output	1x 802.3at PoE+	
USB Power Input	No	
Nominal Power Consumption	NA	
Maximum Power Consumption	18W (w/o PoE)	
Dimensions in inches	1.2 x 4.9 x 11.8 inches	
Dimensions in mm	30 x 124 x 300 mm	
Weight (Pound)	0.96 pounds	
Weight (Gram / Kilogram)	435 grams	
Operating Temperature	-40°–149°F, -40°–65°C	
Humidity	15%–95% (non-condensing)	
Rack-mount	No	
Dual Hot Swap Power Supply	No	

Warranty Info 

---

Warranty	1-Year Limited Warranty
----------	-------------------------