



Quick Look -

Number of Ethernet WAN port 0 / 1 (GE) [1]

[1] Available with PrimeCare Subscription, complimentary for the first year. PrimeCare Enables Ethernet WAN, Wi-Fi WAN, Hot Failover, and Smoothing. Alternatively, without a PrimeCare Subscription, Feature pack license (MAX-BR1-MINI-FP) is required to activate the perpetual license for the aforementioned features.

Number of Ethernet LAN port 3 / 2 (GE) [1]

[1] Available with PrimeCare Subscription, complimentary for the first year. PrimeCare Enables Ethernet WAN, Wi-Fi WAN, Hot Failover, and Smoothing. Alternatively, without a PrimeCare Subscription, Feature pack license (MAX-BR1-MINI-FP) is required to activate the perpetual license for the aforementioned features.

Router Throughput 300Mbps

SpeedFusion VPN Throughput (No

Encryption)

80Mbps

SpeedFusion VPN Throughput (256-

bit AES)

60Mbps [2]

[2] 60 Mbps by default for Firmware 8.4.1 or above.

Number of Cellular Modem

Interfaces -

Maximum Ethernet WAN / LAN port configuration 1 WAN with 2 LAN, 0 WAN with 3 LAN

SFP LAN / WAN No

Serial Interface No

Wi-Fi AP No

Wi-Fi WAN No



USB WAN No

Module Expansion No

Performance -

Number of Recommended Users 1–60

Maximum Number of AP Supported No

Wireless details -

Cellular Modem Category options 1x 5G

5G support Yes

SIM Slots 2

SIM Card Size Nano-SIM (4FF)

Wi-Fi Radio No

Wi-Fi Antenna Transmit Power

(2.4GHz, single chain)

No

Wi-Fi Antenna Transmit Power

(5GHz, single chain)

No

Multiple SSIDs No

GPS No

RemoteSIM (used in SIM Injector) Yes (HW3+)

FusionSIM Yes (HW3+)

Peplink eSIM Data Plans Yes

BYO eSIM Yes

Features -

SpeedFusion Hot Failover Yes [1]

[1] Available with PrimeCare Subscription, complimentary for the first year. PrimeCare Enables Ethernet WAN, Wi-Fi WAN, Hot Failover, and



Smoothing, Alternatively, without a PrimeCare Subscription, Feature pack license (MAX-BR1-MINI-FP) is required to activate the perpetual license for the aforementioned features. $\hbox{\fontsize} \label{thm:complex} \ \hbox{\fontsize} \$ SpeedFusion Smoothing Yes [1] PrimeCare Enables Ethernet WAN, Wi-Fi WAN, Hot Failover, and Smoothing. Alternatively, without a PrimeCare Subscription, Feature pack license (MAX-BR1-MINI-FP) is required to activate the perpetual license for the aforementioned features. Yes [1] [1] Available with PrimeCare Subscription, complimentary for the first year. SpeedFusion Bandwidth Bonding PrimeCare Enables Ethernet WAN, Wi-Fi WAN, Hot Failover, and Smoothing, Alternatively, without a PrimeCare Subscription, Feature pack license (MAX-BR1-MINI-FP) is required to activate the perpetual license for the aforementioned features. [3] PrimeCare subscription includes 500 GB/vear complimentary SpeedFusion Connect Yes [3] SpeedFusion Connect Usage data. SpeedFusion Relay Mode (Server) Yes Drop-In Mode Yes High Availability Yes Peplink AP Series Management No Remote AP & Multiple Config No Profiles Management WAN as LAN Yes LAN Bypass No InTouch Yes Yes [4] [4] 1 Virtual WAN complimentary with active PrimeCare. Up to 3 Virtual Virtual WAN WAN upon purchasing Virtual WAN Activation Licence. Synergy Mode (Controller) Yes Yes Synergized Device Application and Web Blocking Yes Web Content Filtering Lite IP Passthrough Yes

No

IPv6



x.509 Certificate Yes [5] [5] Require IPsec X.509 Certificate License Key

Captive Portal Yes

GPIO Yes

Ignition Sensing Yes

Netflow support Yes

LACP (802.3ad) NIC Bonding No

Internal Storage for Edge No

Computing

External Storage via USB Port No

Dead Reckoning No

Core Functionality

Inter-VLAN Routing Yes

802.1q VLANs Supported 16

Port-Based VLAN Yes

Load Balancing Algorithms 8

Load Balancing & Failover Yes

Inbound Load Balancing No

InControl 2 Cloud Management Yes

InControl GPS Fleet Management No

Advanced QoS Functionality

Bandwidth Usage Monitoring Yes

QoS for VoIP and E-Commerce Yes



User Groups Bandwidth Control Yes

VPN Functionality

SpeedFusion VPN Yes

Number of SpeedFusion VPN Peers 2 or 5 [6] [6] 2 SpeedFusion VPN Peers are enabled by default. 5 SpeedFusion VPN Peers are enabled with PrimeCare Subscription, complimentary for the first

IPsec VPN Yes

Number of IPsec Tunnels 5

L2TP VPN / Open VPN / PPTP VPN Yes

Server

Maximum PPTP / L2TP / OpenVPN

Users

3

Remote RADIUS / LDAP

authentication in Remote User

Access

No

Number of OpenVPN Tunnel (Site to

Site)

Number of GRE Tunnel (Site to Site)

Hardware

Enclosure Compact, **Indoor Metal**

Yes 4pin Molex Micro-Fit Connector

Terminal Block Power Connector for

Mobile / Vehicular Deployment

No

AC Adapter or PSU AC Input 100V-240V,

DC Output 12V 2A

DC 10-30V Input voltage

Yes [7] [7] 1x 802.3at PoE. PoE Input



PoE Output No

USB Power Input No

Nominal Power Consumption 11W

Maximum Power Consumption 13W

Dimensions in inches 4.95 x 4.2 x 1.4 inches

Dimensions in mm 125.7 x 107 x 35 mm

Weight (Pound) 0.93 pounds

Weight (Gram / Kilogram) 420 grams

Operating Temperature -40°-149°F,

-40°-65°C

Humidity 15%–95% (non-condensing)

Rack-mount No

Dual Hot Swap Power Supply No

Warranty Info

Warranty 1-Year Limited Warranty