

HD1 Dome



Quick Look

| | |
|--|---------|
| Number of Ethernet WAN port | No |
| Number of Ethernet LAN port | 1 (GE) |
| Router Throughput | NA |
| SpeedFusion VPN Throughput (No Encryption) | 100Mbps |
| SpeedFusion VPN Throughput (256-bit AES) | 60Mbps |
| Number of Cellular Modem | 1 |

Interfaces

| | |
|---|------------------|
| Maximum Ethernet WAN / LAN port configuration | 0 WAN with 1 LAN |
| SFP LAN / WAN | No |
| Serial Interface | No |
| Wi-Fi AP | No |
| Wi-Fi WAN | No |

| | |
|---------|----|
| USB WAN | No |
|---------|----|

| | |
|------------------|----|
| Module Expansion | No |
|------------------|----|

Performance

| | |
|-----------------------------|--------|
| Number of Recommended Users | 25–150 |
|-----------------------------|--------|

| | |
|--------------------------------|------------------------|
| Maximum Number of AP Supported | 30 / 50 ^[1] |
|--------------------------------|------------------------|

[1] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

| | |
|---------------------------------|-----------------------------------|
| Cellular Modem Category options | 1x CAT-18, 1x CAT-20, 1x 5G |
|---------------------------------|-----------------------------------|

| | |
|------------|-----|
| 5G support | Yes |
|------------|-----|

| | |
|-----------|---|
| SIM Slots | 2 |
|-----------|---|

| | |
|---------------|----------------|
| SIM Card Size | Mini-SIM (2FF) |
|---------------|----------------|

| | |
|-------------|----|
| Wi-Fi Radio | No |
|-------------|----|

| | |
|---|----|
| Wi-Fi Antenna Transmit Power (2.4GHz, single chain) | No |
|---|----|

| | |
|---|----|
| Wi-Fi Antenna Transmit Power (5GHz, single chain) | No |
|---|----|

| | |
|----------------|----|
| Multiple SSIDs | No |
|----------------|----|

| | |
|-----|-----|
| GPS | Yes |
|-----|-----|

| | |
|----------------------------------|-----|
| RemoteSIM (used in SIM Injector) | Yes |
|----------------------------------|-----|

| | |
|-----------|----|
| FusionSIM | No |
|-----------|----|

| | |
|-------------------------|----|
| Peplink eSIM Data Plans | No |
|-------------------------|----|

| | |
|----------|----|
| BYO eSIM | No |
|----------|----|

Features

| | |
|--------------------------|-----|
| SpeedFusion Hot Failover | Yes |
|--------------------------|-----|

| | |
|-----------------------|-----|
| SpeedFusion Smoothing | Yes |
|-----------------------|-----|

| | |
|-------------------------------|-----|
| SpeedFusion Bandwidth Bonding | Yes |
|-------------------------------|-----|

| | |
|---------------------|--------------------|
| SpeedFusion Connect | Yes ^[2] |
|---------------------|--------------------|

^[2] CarePlan subscription includes 1TB/year complimentary SpeedFusion Connect Usage data.

| | |
|---------------------------------|-----|
| SpeedFusion Relay Mode (Server) | Yes |
|---------------------------------|-----|

| | |
|--------------|----|
| Drop-In Mode | No |
|--------------|----|

| | |
|-------------------|-----|
| High Availability | Yes |
|-------------------|-----|

| | |
|------------------------------|-----|
| Peplink AP Series Management | Yes |
|------------------------------|-----|

| | |
|---|----|
| Remote AP & Multiple Config Profiles Management | No |
|---|----|

| | |
|------------|----|
| WAN as LAN | No |
|------------|----|

| | |
|------------|----|
| LAN Bypass | No |
|------------|----|

| | |
|---------|-----|
| InTouch | Yes |
|---------|-----|

| | |
|-------------|--------------------|
| Virtual WAN | Yes ^[3] |
|-------------|--------------------|

^[3] Up to 3 Virtual WAN upon purchasing Virtual WAN Activation Licence.

| | |
|---------------------------|-----|
| Synergy Mode (Controller) | Yes |
|---------------------------|-----|

| | |
|-------------------|-----|
| Synergized Device | Yes |
|-------------------|-----|

| | |
|------------------------------|-----|
| Application and Web Blocking | Yes |
|------------------------------|-----|

| | |
|-----------------------|------|
| Web Content Filtering | Lite |
|-----------------------|------|

| | |
|-------------------------------------|-----|
| IP Passthrough | Yes |
| IPv6 | Yes |
| x.509 Certificate | Yes |
| Captive Portal | Yes |
| GPIO | No |
| Ignition Sensing | No |
| Netflow support | Yes |
| LACP (802.3ad) NIC Bonding | No |
| Internal Storage for Edge Computing | No |
| External Storage via USB Port | No |
| Dead Reckoning | No |

Core Functionality

| | |
|------------------------------|-----|
| Inter-VLAN Routing | Yes |
| 802.1q VLANs Supported | 128 |
| Port-Based VLAN | Yes |
| Load Balancing Algorithms | 8 |
| Load Balancing & Failover | Yes |
| Inbound Load Balancing | No |
| InControl 2 Cloud Management | Yes |

| | |
|--------------------------------|-----|
| InControl GPS Fleet Management | Yes |
|--------------------------------|-----|

Advanced QoS Functionality

| | |
|----------------------------|-----|
| Bandwidth Usage Monitoring | Yes |
|----------------------------|-----|

| | |
|-----------------------------|-----|
| QoS for VoIP and E-Commerce | Yes |
|-----------------------------|-----|

| | |
|-------------------------------|-----|
| User Groups Bandwidth Control | Yes |
|-------------------------------|-----|

VPN Functionality

| | |
|-----------------|-----|
| SpeedFusion VPN | Yes |
|-----------------|-----|

| | |
|---------------------------------|---|
| Number of SpeedFusion VPN Peers | 2 |
|---------------------------------|---|

| | |
|-----------|-----|
| IPsec VPN | Yes |
|-----------|-----|

| | |
|-------------------------|---|
| Number of IPsec Tunnels | 5 |
|-------------------------|---|

| | |
|---------------------------------------|-----|
| L2TP VPN / Open VPN / PPTP VPN Server | Yes |
|---------------------------------------|-----|

| | |
|-------------------------------------|----|
| Maximum PPTP / L2TP / OpenVPN Users | 15 |
|-------------------------------------|----|

| | |
|---|-----|
| Remote RADIUS / LDAP authentication in Remote User Access | Yes |
|---|-----|

| | |
|---|---|
| Number of OpenVPN Tunnel (Site to Site) | 5 |
|---|---|

| | |
|-------------------------------------|---|
| Number of GRE Tunnel (Site to Site) | 5 |
|-------------------------------------|---|

Hardware

| | | |
|--|--|---------------------|
| Enclosure | Outdoor, IP67, Metal | |
| 4pin Molex Micro-Fit Connector | No | |
| Terminal Block Power Connector for Mobile / Vehicular Deployment | No | |
| AC Adapter or PSU | No | |
| Input voltage | PoE: DC 48–56V | |
| PoE Input | Yes ^[4] | [4] 1x 802.3at PoE. |
| PoE Output | 1x 802.3af PoE (with Ethernet Splitter) | |
| USB Power Input | No | |
| Nominal Power Consumption | NA | |
| Maximum Power Consumption | 20W | |
| Dimensions in inches | 4.33 inches (radius) x 4.53 inches (height) | |
| Dimensions in mm | 110 mm (radius) x 115 mm (height) | |
| Weight (Pound) | With Ethernet Splitter: 3.75 pounds, Without Ethernet Splitter: 2.65 pounds | |
| Weight (Gram / Kilogram) | With Ethernet Splitter: 1.7 kg, Without Ethernet Splitter: 1.2 kg | |
| Operating Temperature | -40°–149°F, -40°–65°C | |



| | |
|----------|--------------------------|
| Humidity | 15%–95% (non-condensing) |
|----------|--------------------------|

| | |
|------------|----|
| Rack-mount | No |
|------------|----|

| | |
|----------------------------|----|
| Dual Hot Swap Power Supply | No |
|----------------------------|----|

Warranty Info

| | |
|----------|-------------------------|
| Warranty | 1-Year Limited Warranty |
|----------|-------------------------|