



Quick Look

Number of Ethernet WAN port	1 (GE)	
Number of Ethernet LAN port	2 (GE)	
Router Throughput	300Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (No Encryption)	100Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
SpeedFusion VPN Throughput (256-bit AES)	60Mbps ^[1]	[1] Router Throughput and PepVPN/SpeedFusion Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.
Number of Cellular Modem	2	

Interfaces

Maximum Ethernet WAN / LAN port configuration	1 WAN with 2 LAN, 0 WAN with 3 LAN
SFP LAN / WAN	No
Serial Interface	Yes
Wi-Fi AP	No
Wi-Fi WAN	No
USB WAN	Yes (1x USB)

Module Expansion	No
------------------	----

Performance

Number of Recommended Users	25–150
-----------------------------	--------

Maximum Number of Controlled AP / Switch	30 / 50 ^[2]	[2] 50 AP is available as a license add-on (AP-LC-50).
------------------------------------------	-------------------------------	--------------------------------------------------------

Wireless details

Cellular Modem Category options	2x CAT-4, 2x CAT-6
---------------------------------	-------------------------------

5G support	No
------------	----

SIM Slots	4
-----------	---

SIM Card Size	Mini-SIM (2FF)
---------------	----------------

Wi-Fi Radio	No
-------------	----

Wi-Fi Antenna Transmit Power (2.4GHz, single chain)	No
--------------------------------------------------------	----

Wi-Fi Antenna Transmit Power (5GHz, single chain)	No
---------------------------------------------------	----

Multiple SSIDs	No
----------------	----

GPS Yes

RemoteSIM (used in SIM Injector)	Yes (HW2+) ^[3]	[3] RemoteSIM and FusionSIM are only available for MAX-HD2-MINI-XXXX-RM-T.
----------------------------------	----------------------------------	----------------------------------------------------------------------------

FusionSIM	Yes (HW2+) ^[3]	[3] RemoteSIM and FusionSIM are only available for MAX-HD2-MINI-XXXX-RM-T.
-----------	---------------------------	----------------------------------------------------------------------------

Peplink eSIM Data Plans	Yes (HW4+) ^[4]	^[4] Require Firmware 8.3.0 or above and supported for selected SKU.
-------------------------	----------------------------------	--------------------------------------------------------------------------------

BYO eSIM	Yes (HW4+) ^[4]	[4] Require Firmware 8.3.0 or above and supported for selected SKU.
----------	---------------------------	---------------------------------------------------------------------

Features

SpeedFusion Hot Failover **Yes**SpeedFusion Smoothing **Yes**SpeedFusion Bandwidth Bonding **Yes**SpeedFusion Connect **Yes** ^[5]

[5] SpeedFusion Connect is only available for MAX-HD2-MINI-XXXX-RM-T.CarePlan subscription includes 1TB/year complimentary SpeedFusion Connect Usage data.

SpeedFusion Relay Mode (Server) **Yes**Drop-In Mode **Yes**High Availability **Yes**Peplink AP Series Management **Yes**Remote AP & Multiple Config
Profiles Management **No**Switch Controller **Yes**WAN as LAN **Yes**LAN Bypass **No**InTouch **Yes**Virtual WAN **Yes** ^[6]

[6] Up to 3 Virtual WAN upon purchasing Virtual WAN Activation Licence.

Synergy Mode (Controller) **Yes**Synergized Device **Yes**Application and Web Blocking **Yes**Web Content Filtering **Lite**IP Passthrough **Yes** ^[7]

[7] Available for Firmware 8.5.0 or above.

IPv6 **Yes**x.509 Certificate **Yes**

Captive Portal	Yes
GPIO	No
Ignition Sensing	No
Netflow Support	Yes
LACP (802.3ad) NIC Bonding	No
Jumbo Frame Support	Yes
Internal Storage for Edge Computing	No
External Storage via USB Port	No
Dead Reckoning	No

Core Functionality

Inter-VLAN Routing	Yes
802.1q VLANs Supported	128
Port-Based VLAN	Yes
Load Balancing Algorithms	8
Load Balancing & Failover	Yes
Inbound Load Balancing	No
InControl 2 Cloud Management	Yes
InControl GPS Fleet Management	Yes

Advanced QoS Functionality

Bandwidth Usage Monitoring	Yes
QoS for VoIP and E-Commerce	Yes

User Groups Bandwidth Control	Yes
-------------------------------	-----

VPN Functionality

SpeedFusion VPN	Yes
-----------------	-----

Number of SpeedFusion VPN Peers	2 or 20 ^[8]
---------------------------------	------------------------

[8] Require license to increase maximum number of PepVPN/SpeedFusion Peers. Several option are available based on the model 5, 10 or 20 peers (PVN-LC-05, PVN-LC-10, PVN-LC-20).

IPsec VPN	Yes
-----------	-----

Number of IPsec Tunnels	5
-------------------------	---

L2TP VPN / Open VPN / PPTP VPN Server	Yes
---------------------------------------	-----

Maximum PPTP / L2TP / OpenVPN Users	15
-------------------------------------	----

Remote RADIUS / LDAP authentication in Remote User Access	Yes
-----------------------------------------------------------	-----

Number of OpenVPN Tunnel (Site to Site)	5
-----------------------------------------	---

Number of GRE Tunnel (Site to Site)	5
-------------------------------------	---

Hardware

Enclosure	Indoor, Metal
-----------	------------------

4pin Molex Micro-Fit Connector	No
--------------------------------	----

Terminal Block Power Connector for Mobile / Vehicular Deployment	Yes
------------------------------------------------------------------	-----

AC Adapter or PSU	AC Input 100V–240V, DC Output 12V 3A
-------------------	-----------------------------------------

Input voltage	DC 10–56V
---------------	-----------

PoE Input	Yes ^[9]
-----------	--------------------

[9] 1x 802.3at PoE.

PoE Output	Up to 2x 802.3at PoE+ ^[10]	[10] Require PoE Activation Kit. Includes power supply and license to enable PoE Output Ports.
USB Power Input	No	
Nominal Power Consumption	NA	
Maximum Power Consumption	15W (w/o PoE)	
Dimensions in inches	1.6 x 5.8 x 5 inches	
Dimensions in mm	40 x 147 x 129 mm	
Weight (Pound)	1.32 pounds	
Weight (Gram / Kilogram)	0.6 kg	
Operating Temperature	-40°–149°F, -40°–65°C	
Humidity	15%–95% (non-condensing)	
Rack-mount	No	
Dual Hot Swap Power Supply	No	

Warranty Info

Warranty	1-Year Limited Warranty
----------	-------------------------