





Quick Look

- Number of Ethernet WAN port
2 (GE)
- Number of Ethernet LAN port
7 (GE)
- Router Throughput
2.5Gbps
- SpeedFusion VPN Throughput (No Encryption)
600Mbps
- SpeedFusion VPN Throughput (256-bit AES)
500Mbps
- Number of Cellular Modem
4

Interfaces

- Maximum Ethernet WAN / LAN port configuration
2 WAN with 7 LAN
- SFP LAN / WAN
No
- Serial Interface
No
- Wi-Fi AP
Yes
- Wi-Fi WAN
Yes
- USB WAN
Yes (1x USB)
- Module Expansion
No

Performance

Number of Recommended Users
50-500
Maximum Number of AP Supported
30 / 50
[1]
[1] 50 AP is available as a license add-on (AP-LC-50).

Wireless details

Cellular Modem Category options
4x CAT-12, 2x 5G
5G support
Yes
SIM Slots
4 + 4 redundant slots
SIM Card Size
Nano-SIM (4FF)
Wi-Fi Radio
Dual (2.4GHz + 5GHz), 2x2 Wi-Fi 5
Wi-Fi Antenna Transmit Power (2.4GHz, single chain)
24dBm
Wi-Fi Antenna Transmit Power (5GHz, single chain)
21dBm
Multiple SSIDs
16
GPS
Yes
RemoteSIM (used in SIM Injector)
Yes
FusionSIM
Yes
Peplink eSIM Data Plans
Yes
[2]
[2] Require Firmware 8.3.0 or above.
BYO eSIM
Yes
[3]
[3] Require Firmware 8.4.0 or above.

Features

SpeedFusion Hot Failover
Yes
SpeedFusion Smoothing
Yes
SpeedFusion Bandwidth Bonding
Yes
SpeedFusion Connect
Yes
[4]
[4] CarePlan subscription includes 2.5TB/year complimentary SpeedFusion Connect Usage data.
SpeedFusion Relay Mode (Server)
Yes
Drop-In Mode
Yes
High Availability
Yes
Peplink AP Series Management
Yes
Remote AP & Multiple Config Profiles Management

No

WAN as LAN

No

LAN Bypass

No

InTouch

Yes

Virtual WAN

Yes

[5]

[5] Up to 3 Virtual WAN if purchasing Virtual WAN Activation Licence.

Synergy Mode (Controller)

Yes

Synergized Device

Yes

Application and Web Blocking

Yes

Web Content Filtering

Lite

IP Passthrough

Yes

[6]

[6] Available for Firmware 8.5.0 or above.

IPv6

Yes

x.509 Certificate

Yes

Captive Portal

Yes

GPIO

No

Ignition Sensing

No

Netflow support

Yes

LACP (802.3ad) NIC Bonding

Yes

[7]

[7] Require Firmware 8.4.1 or above.

Internal Storage for Edge Computing

Optional

[8]

[8] Please contact Peplink Business Development team for details.

External Storage via USB Port

Yes

[9]

[9] Support Docker.

Dead Reckoning

Yes

Core Functionality

Inter-VLAN Routing

Yes

802.1q VLANs Supported

128

Port-Based VLAN

Yes

Load Balancing Algorithms

8

Load Balancing & Failover

Yes
Inbound Load Balancing
No
InControl 2 Cloud Management
Yes
InControl GPS Fleet Management
Yes

Advanced QoS Functionality

Bandwidth Usage Monitoring
Yes
QoS for VoIP and E-Commerce
Yes
User Groups Bandwidth Control
Yes

VPN Functionality

SpeedFusion VPN
Yes
Number of SpeedFusion VPN Peers
3 or 20
[10]
[10] Require license to increase maximum number of PepVPN/SpeedFusion Peers. Several option are available based on the model 5, 10 or 20 peers (PVN-LC-05, PVN-LC-10, PVN-LC-20).
IPsec VPN
Yes
Number of IPsec Tunnels
5
L2TP VPN / Open VPN / PPTP VPN Server
Yes
Maximum PPTP / L2TP / OpenVPN Users
15
Remote RADIUS / LDAP authentication in Remote User Access
Yes
Number of OpenVPN Tunnel (Site to Site)
5
Number of GRE Tunnel (Site to Site)
5

Hardware

Enclosure
Pelican case
4pin Molex Micro-Fit Connector
No
Terminal Block Power Connector for Mobile / Vehicular Deployment
No
AC Adapter or PSU
No
Input voltage
DC 12–56V, AC 100–240V
PoE Input
No
PoE Output
Up to 7x 802.3at PoE+
USB Power Input
No
Nominal Power Consumption

NA

Maximum Power Consumption
38W (w/o PoE)

Dimensions in inches
19.78 x 15.77 x 7.41 inch

Dimensions in mm
502 x 401 x 188 mm

Weight (Pound)
34.53 pounds

Weight (Gram / Kilogram)
15.68 kg

Operating Temperature
-40°–113°F, -40°–45°C

Humidity
15%–95% (non-condensing)

Rack-mount
No

Dual Hot Swap Power Supply
No

Warranty Info

Warranty
1-Year Limited Warranty